



**MINI FOREST**



**MINI FOREST RANGE**  
NO COMPROMISE





**MANUFACTURED BY OSMA.**  
**40 YEARS OF QUALITY..GUARANTEED!**



## Technical

Model	Excavator Weight Range (Tonnes)	Mulcher Weight w/o Bracket (kg)	Oil Flow Requirement (L/min)	Max Hyd Circuit Pressure (bar)	Cut Width (mm)	Max Cut Diameter (mm)	Rotor Type	Standard Motor Size (cc)	Total Width (mm)
TFK70	2.5-5	285	30	220-250	700	150	Fixed tool rotor	17	880
TFK90	4-6	335	45	220-250	900	150	Fixed tool rotor	17	1080
TF80XL-CQ	5-10	525	50-75	220-250	800	200	Fixed tool rotor	34	1000
TF100XL-CQ	5-14	575	60-110	220-250	1000	200	Fixed tool rotor	34	1200



**TFK70**



**TF100 XL**





## AT A GLANCE

- 'Depth Control Rotor (DCR) for maximum efficiency'
- To suit excavators from 2.5 to 14 tonnes (std configuration). Also available for compact loader & skid steer applications.
- Cut capability for grass and vegetation up to 200mm diameter.
- Heavy duty casing manufactured from Weldox 700 steel for maximum strength and durability.
- Internal frame and counter blades manufactured from Hardox 400.
- Piston motor gives optimum power output.
- Multi-belt transmission.
- Hydraulic operation of front cover.
- Manufactured by Osma..45 years of quality guaranteed!



**TF100 XL**



**DC  
ROTOR**  
30% MORE EFFICIENCY

---

# MINI FOREST

No Compromise

---

## MINI FOREST

- Vegetation Control.
- Site Clearance.
- Thinning Operations.
- Embankment Maintenance.
- Whole Trees, Scrub, Grass.
- Boundary Restoration.
- Woodland Maintenance.



---

Exac-One Ltd  
The Mount Buildings  
Tunnel Hill  
Upton on Severn  
Worcestershire  
WR8 0QL  
UK



NJ based EXAC-ONE distributor  
Ph. 888-280-1710  
[sales@ransomeattach.com](mailto:sales@ransomeattach.com)