



MINI MOWER



MINI MOWER RANGE
NO COMPROMISE

Manufactured by Osma.
40 years of quality...guaranteed!



Technical

| Model | Excavator Weight Range (Tonnes) | Mower Weight w/o Bracket (kg) | Oil Flow Requirement (L/min) | Max Hyd Circuit Pressure (bar) | Cut Width (mm) | Max Cut Diameter (mm) | Standard Rotor Type | Standard Motor Size (cc) | Total Width (mm) |
|----------|---------------------------------|-------------------------------|------------------------------|--------------------------------|----------------|-----------------------|---------------------|--------------------------|------------------|
| TE60 DXL | 1-2 | 70 | 20-30 | 160 | 600 | 10 | TYPE H | 8 | 800 |
| TE80 DXL | 1.5-2.5 | 85 | 20-30 | 160 | 800 | 10 | TYPE H | 8 | 1000 |
| TE80 DL | 2-3.5 | 100 | 30-45 | 170 | 800 | 50 | TYPE RM7 | 11 | 1000 |
| TE100 DL | 2.5-4 | 120 | 30-50 | 170 | 1000 | 50 | TYPE RM7 | 16 | 1150 |
| TE80 DP | 2.5-5 | 170 | 30-50 | 180 | 800 | 50 | TYPE RM7 | 11 | 1100 |
| TE100 DP | 2.5-5 | 195 | 40-60 | 180 | 1000 | 50 | TYPE RM7 | 16 | 1300 |
| TE120 DP | 4-8 | 230 | 50-70 | 180 | 1200 | 50 | TYPE C | 22 | 1500 |
| TE100 CL | 6-10 | 315 | 60-70 | 190-200 | 1050 | 70 | TYPE C | 34 | 1250 |
| TE120 CL | 6-10 | 345 | 60-70 | 190-200 | 1250 | 70 | TYPE C | 34 | 1400 |

TE80 DXL



TE80 DP

AT A GLANCE

- To suit excavators from 1 – 10 tonne (std configuration) also available for loaders and skid steers.
- Cut capability for grass and vegetation up to 70mm diameter.
- Manufactured using high grade structural and wear resistant steels, for exceptional strength and durability.
- Adjustable rear roller.
- Choice of flails (does not apply to DXL models).
- Options – floating link, flow control valve, jack stand.
- Manufactured by Osma...40 years of quality guaranteed!



TE120 DP

