



MINI MOWER



MINI MOWER RANGE
NO COMPROMISE

RA RANSOME
ATTACHMENTS

EX-K1
One

Manufactured by Osma.
45 years of quality...guaranteed!



Technical

Model	Excavator Weight Range (Tonnes)	Mower Weight w/o Bracket (kg)	Oil Flow Requirement (L/min)	Max Hyd Circuit Pressure (bar)	Cut Width (mm)	Max Cut Diameter (mm)	Standard Rotor Type	Standard Motor Size (cc)	Total Width (mm)
MM60L	1-2	70	20-30	160	600	10	TYPE H	8	800
MM80L	1.5-2.5	85	20-30	160	800	10	TYPE H	8	1000
MM80M	2.5-7	170	30-50	180	800	50	TYPE RM7	11	1100
MM100M	2.5-7	195	40-60	180	1000	50	TYPE RM7	16	1300
MM120M	4-8	230	50-70	180	1200	50	TYPE C	22	1500
MM100H	6-10	315	60-70	190-200	1050	70	TYPE C	34	1250
MM120H	6-10	345	60-70	190-200	1250	70	TYPE C	34	1400

MM80L



MM80M

AT A GLANCE

- To suit excavators from 1 – 10 tonne (std configuration) also available for loaders and skid steers.
- Cut capability for grass and vegetation up to 70mm diameter.
- Manufactured using high grade structural and wear resistant steels, for exceptional strength and durability.
- Adjustable rear roller.
- Choice of flails (does not apply to DXL models).
- Options – floating link, flow control valve, jack stand.
- Manufactured by Osma.. 45 years of quality guaranteed!



MM120M





Ph. 888-280-1710

sales@ransomeattach.com

ransomeattach.com

MINI MOWER

No Compromise

MINI MOWER

- Vegetation Control.
- Site Clearance.
- Thinning Operations.
- Embankment Maintenance.
- Hedges, Scrub, Grass.
- Boundary Restoration.
- Woodland Maintenance.

JAN 2023



Exac-One Ltd
The Mount Buildings
Tunnel Hill
Upton on Severn
Worcestershire
WR8 0QL
UK

+44 (0)1684 593052

www.exac-one.co.uk
info@exac-one.co.uk